

DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE				
Dina Cina and Wainlet	0.0/0 0.05DDf		$\overline{}$	
Pipe Size and Weight: Pipe Grade:	2.3/8" x 6.65PPf X	_	-01 -	<u>-</u> i
Range:	2	_	· \	3.375" OD
Tool Joint:	3-3/8" x 1-3/4" NC26	—		
Tool Joint.	3-3/8 X 1-3/4 NC20	-		
PIPE			}	
Dimensional Data	New			
OD (in)	2.375			1.750" ID
Wall thickness (in)	0.28		- 1 <i>1</i>	1.700 15
Minimum wall (%)	95.0			i
ID (in)	1.815			į [
Cross sectional area pipe body (in²)	1.843			<u> </u>
Cross sectional area OD (in²)	4.430			
Cross sectional area ID (in²)	2.587			i
Section modulus (in³)	0.867			į [
Polar section modulus (in ³)	1.733			į [
	•••			2.375"OD
Performance Data	New			
Torsional strength (ft-lbs)	7,917			i
Tensile strength (lbs)	175,072			į l
80% Torsional strength (ft-lbs)	6,334			!
Burst Pressure capacity (psi)	19,600	31.5.		
Collapse capacity (psi)	19,759	რ		
, , , , , , , , , , , , , , , , , , ,	,			i
TOOL JOINT				
Dimensional Data	New			i 1.815" ID
OD (in)	3.375			
ID (in)	1.750			
Pin tong length (in)	9			i
Box tong length (in)	10			į
Connection	NC26			!
Performance Data	New			i
Torsional Strength (ft-lbs)	6,875			į l
Max Recommended Make-up Torque (ft-lbs)	4,125			ļ.
Min Recommended Make-up Torque (ft-lbs)	3,094			1.750" ID
Tensile strength (lbs)	313,681			\
Tool joint/Drill pipe torsional ratio (New pipe)	0.87		$\overline{}$	
			1	X
			_ 6	K !
Drill pipe assembly with NC26 tool joint				
Average length (ft)	31.5		_ <u>~</u> \	
Drift size (in)	1.625		\	I ∷
			\	
			_	
				I

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information. All data described are the users own risk & responsibility.