

DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE				
Pipe Size and Weight:	4" x 14.0 PPf	-	\uparrow	 _
Pipe Grade:	S	-	15.5"	
Range:	RII		# #	5.00" OI
Tool Joint:	5" x 2.563" DPHT38	-	\downarrow \mid \sqsubseteq	`
1001001111	0 X 2.000 D111100	-		7
PIPE		7) [
Dimensional Data	New		1.7	
OD (in)	4.000		1/	2.563" ID
Wall thickness (in)	0.33		17	
Minimum wall (%)	95.0			!
ID (in)	3.34			
Cross sectional area pipe body (in²)	3.805			
Cross sectional area OD (in²)	12.566			
Cross sectional area ID (in²)	8.762			.
Section modulus (in³)	3.229			!
Polar section modulus (in³)	6.458	_		
Portonno Doto	No	_		< 4"OD
Performance Data	New	- 		
Torsional strength (ft-lbs)	41,918	_		
Tensile strength (lbs)	513,646			
80% Torsional strength (ft-lbs)	33,534	31.5.		i
Burst Pressure capacity (psi)	19,491	— <u>ε</u>		<u> </u>
Collapse capacity (psi)	20,137	-		
TOOL JOINT		-		0.040".15
Dimensional Data	New		←	3.340" ID
OD (in)	5.000			
ID (in)	2.563			i
Pin tong length (in)	10			<u> </u>
Box tong length (in)	15.5			<u> </u>
Connection	DPHT38	_		
Performance Data	New			
Torsional Strength (ft-lbs)	29,667	- 		
Max Recommended Make-up Torque (ft-lbs)	17,800			i
Min Recommended Make-up Torque (ft-lbs)	13,350	—		2.563" ID
Tensile strength (lbs)	634,557	-	\	/
Tool joint/Drill pipe torsional ratio (New pipe)	0.71	-	/	ł X
p.p.	•			/]
		_	[10] F	
Drill pipe assembly with DPHT38 tool joint		\dashv		
Average length (ft)	31.5		_	
Drift size (in)	2.438	—	\	. 7
			\	! <i> </i>
		1	<u>I</u>	¦ -J

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information.