

## DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE		
Pipe Size and Weight:	4" x 15.7 PPf	
Pipe Grade:	G	
Range:	RII	5.25" OD
Tool Joint:	5.1/4" x 2.688" DPDS40	
PIPE		
Dimensional Data	New	
OD (in)	4.000	2.688" ID
Wall thickness (in)	0.38	
Minimum wall (%)	95.0	
ID (in)	3.24	
Cross sectional area pipe body (in²)	4.322	
Cross sectional area OD (in <sup>2</sup> )	12.566	_
Cross sectional area ID (in <sup>2</sup> )	8.245	
Section modulus (in <sup>3</sup> )	3.578	
Polar section modulus (in <sup>3</sup> )	7.157	
Daufarmanaa Data	New	4"OD
Performance Data	New 26 124	
Torsional strength (ft-lbs)	36,134	
Tensile strength (lbs)	453,765	
80% Torsional strength (ft-lbs) Burst Pressure capacity (psi)	28,907	- i i
Collapse capacity (psi)	<u> </u>	— <del>6</del>   i
	18,055	
TOOL JOINT		
Dimensional Data	New	— <u>i 3.240"</u> ID
OD (in)	5.250	
ID (in)	2.688	
Pin tong length (in)	9	
Box tong length (in)	12	
Connection	DPDS40	
Performance Data	New	-1     !
Torsional Strength (ft-lbs)	32,667	-1
Max Recommended Make-up Torque (ft-lbs)	19,600	2.688" ID
Min Recommended Make-up Torque (ft-lbs)	14,700	
Tensile strength (lbs) Tool joint/Drill pipe torsional ratio (New pipe)	776,200 0.90	-1 $ $ $ $ $ $ $ $ $ $ $ $ $ $
	0.90	$\neg   \neg \uparrow   \downarrow / \uparrow$
Drill pipe assembly with DPDS40 tool joint		
Average length (ft)	31.5	╶┨ <u>坐<u></u>└┐│¦═╤┙</u>
Drift size (in)	2.563	-1 \ \ ├//
Note:		┓ \ ; /
Hard banding: Duraband / Arnco 100XT		
Make & Break: 3 Cycles		
Internal Plastic coating: JSU 3		

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information.