

DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE		
Pipe Size and Weight:	4" x 14.0 PPf	
Pipe Grade:	S	
Range:	2	
Tool Joint:	5.1/4" x 2.563" NC40	
		—
PIPE	Na	
Dimensional Data OD (in)	New 4.000	
Wall thickness (in)	0.33	2.563" ID
Minimum wall (%)	95.0	─
ID (in)	3.34	-
ום (וח) Cross sectional area pipe body (in²)	3.805	⊣
Cross sectional area pipe body (in²) Cross sectional area OD (in²)	12.566	
Cross sectional area ID (in²)	8.762	⊣
Section modulus (in³)	3.229	⊣
Polar section modulus (in³)	3.229 6.458	⊣
roiai section modulus (m²)	0.400	
Performance Data	New	<u> </u>
Torsional strength (ft-lbs)	41,918	-
Tensile strength (lbs)	513,646	-
80% Torsional strength (ft-lbs)	33,534	⊣ <u> </u>
Burst Pressure capacity (psi)	19,491	
Collapse capacity (psi)	20,141	<u> </u>
Conapos capacity (poly	20,111	
TOOL JOINT		
Dimensional Data	New	i 3.340" ID
OD (in)	5.250	
ID (in)	2.563	
Pin tong length (in)	9	
Box tong length (in)	12	
Connection	NC40	
Performance Data	New	
Torsional Strength (ft-lbs)	27,752	
Max Recommended Make-up Torque (ft-lbs)	16,651	
Min Recommended Make-up Torque (ft-lbs)	12,488	2.563" ID
Tensile strength (lbs)	838,257	
Tool joint/Drill pipe torsional ratio (New pipe)	0.66	
Drill pipe assembly with NC40 tool joint		
Average length (ft)	31.5	
Drift size (in)	2.438	→ \ 🗇
Note: Internal Plastic Coating: JSU3		\ i
Hard banding: Duraband / Arnco 100XT		\ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information. All data described are the users own risk & responsibility.