

DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

Pipe Size and Weight: 5-1/2" x 24.7 PPf Pipe Grade: S Range: 2 Tool Joint: 7.00" x 4.0" 5-1/2FH PIPE Dimensional Data New OD (in) 5.500 Wall thickness (in) 0.415 Minimum wall (%) 95.0 ID (in) 4.67
Pipe Grade: S Range: 2 Tool Joint: 7.00" x 4.0" 5-1/2FH PIPE New Dimensional Data New Wall thickness (in) 0.415 Minimum wall (%) 95.0
Range: 2
Tool Joint: 7.00" x 4.0" 5-1/2FH New
PIPE Dimensional Data
Dimensional Data New OD (in) 5.500 Wall thickness (in) 0.415 Minimum wall (%) 95.0
OD (in) 5.500 Wall thickness (in) 0.415 Minimum wall (%) 95.0
Wall thickness (in) 0.415 Minimum wall (%) 95.0
Minimum wall (%) 95.0
, ,
ID (in) 4.67
Cross sectional area pipe body (in²) 6.630
Cross sectional area OD (in²) 23.758
Cross sectional area ID (in²) 17.129
Section modulus (in³) 7.844
Polar section modulus (in³) 15.688
Performance Data New
Torsional strength (ft-lbs) 101,834
Tensile strength (lbs) 894,999
80% Torsional strength (ft-lbs) 81,467
Burst Pressure capacity (psi) 17,826
Collapse capacity (psi) 17,019
TOOL JOINT
Dimensional Data New
OD (in) 7.000
<i>ID (in)</i> 4.000
Pin tong length (in) 10
Box tong length (in) 12
Connection 5-1/2FH
Performance Data New
Torsional Strength (ft-lbs) 55,933
Max Recommended Make-up Torque (ft-lbs) 33,560
Min Recommended Make-up Torque (ft-lbs) 25,170
Tensile strength (lbs) 1,265,802
Tool joint/Drill pipe torsional ratio (New pipe) 0.55
Drill pipe assembly with 5-1/2FH tool joint
Average length (ft) 31.5
Drift size (in) 3.875

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information.