

## DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE		
Pipe Size and Weight:	4" x 14.0 PPf	
Pipe Grade:	G	5.25" OD
Range:	RII	
Tool Joint:	5.1/4" x 2.563" DPDS40	
PIPE		<b>-</b>   \ \ <del> </del> /
Dimensional Data	New	1
OD (in)	4.000	2.563" ID
Wall thickness (in)	0.33	
Minimum wall (%)	95.0	<b>1</b>
ID (in)	3.34	<b>- </b>
Cross sectional area pipe body (in²)	3.805	1
Cross sectional area OD (in²)	12.566	1
Cross sectional area ID (in²)	8.762	<b>1</b>
Section modulus (in³)	3.229	<b> </b>
Polar section modulus (in³)	6.458	<b> </b>
		-         4"OD
Performance Data	New	1
Torsional strength (ft-lbs)	32,603	1
Tensile strength (lbs)	399,502	<b>- </b>
80% Torsional strength (ft-lbs)	26,082	<b>1</b>   _    !
Burst Pressure capacity (psi)	15,159	-   18 -   5.     1
Collapse capacity (psi)	15,896	]   "
	·	<b>1</b>
TOOL JOINT		<b>1</b>
Dimensional Data	New	3.340" ID
OD (in)	5.250	]     `
ID (in)	2.563	]
Pin tong length (in)	9	]
Box tong length (in)	12	]
Connection	DPDS40	]
Performance Data	New	
Torsional Strength (ft-lbs)	36,333	<b>- </b>
Max Recommended Make-up Torque (ft-lbs)	21,800	<b>- </b>
Min Recommended Make-up Torque (ft-lbs)	16,350	
Tensile strength (lbs)	838,300	1
Tool joint/Drill pipe torsional ratio (New pipe)	1.11	1   <u>_</u> /   <i>X</i>
	·	<u>ි</u> ව
Drill pipe assembly with DPDS40 tool joint	04.5	┩
Average length (ft)	31.5	┦ <u>, , , , , , , , , , , , , , , , , , ,</u>
Drift size (in)	2.438	┥ \   ⊡
Note:		\
Hard banding: Duraband / Arnco 100XT Make & Break: 3 Cycles		
Internal Plastic coating: JSU 3		
internal Flustic country, 000 5		

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information. All data described are the users own risk & responsibility.