

DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE			
Pipe Size and Weight:	5" x 25.6PPf		
Pipe Grade:	S-135	6.625" OD	
Range:	2		
Tool Joint:	6.5/8" x 2.75" NC50	<u> </u>	
DIDE			
PIPE Dimensional Data	New	─	
OD (in)	5.000		
Wall thickness (in)	0.5		
Minimum wall (%)	95.0	─	
ID (in)	4	─	
Cross sectional area pipe body (in²)	7.069	 	
Cross sectional area OD (in²)	19.635	 	
Cross sectional area ID (in²)	12.566	 	
Section modulus (in³)	7.245	─	
Polar section modulus (in³)	14.491	─	
, , , , , , , , , , , , , , , , , , , ,	1117		
Performance Data	New		
Torsional strength (ft-lbs)	94,062	—	
Tensile strength (lbs)	954,259		
80% Torsional strength (ft-lbs)	75,250		
Burst Pressure capacity (psi)	23,625		
Collapse capacity (psi)	24,300		
		 	
TOOL JOINT (Minimum yield strength: 120KSI).			
Dimensional Data	New		
OD (in)	6.625	─	
ID (in)	2.750 9	─	
Pin tong length (in)		─	
Box tong length (in) Connection	12 NC50	─	
Connection	NC50	 	
Performance Data	New	 	
Torsional Strength (ft-lbs)	63,406	 	
Max Recommended Make-up Torque (ft-lbs)	38,044		
Min Recommended Make-up Torque (ft-lbs)	28,533		
Tensile strength (lbs)	1,551,706		
Tool joint/Drill pipe torsional ratio (New pipe)	0.67		
		<u> </u>	
Drill pipe assembly with NC50 tool joint			
Average length (ft)	31.5		
Drift size (in)	2.625	_	
		\	
		\ \\	
		1	

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information. All data described are the users own risk & responsibility.