

DRILL PIPE PERFORMANCE CHARACTERISTICS SHEET

DRILL PIPE	
Pipe Size and Weight:	5-7/8" x 23.4 PPf
Pipe Grade:	S
Range: Tool Joint:	2
Tool Joint:	7.00" x 4.0" DPDS55
PIPE	
Dimensional Data	New
OD (in)	5.875
Wall thickness (in)	0.361
Minimum wall (%)	95.0
ID (in)	5.153
Cross sectional area pipe body (in ²)	6.254
Cross sectional area OD (in ²)	27.109
Cross sectional area ID (in²)	20.855
Section modulus (in ³)	8.125
Polar section modulus (in ³)	16.251
Performance Data	New
Torsional strength (ft-lbs)	105,489
Tensile strength (lbs)	844,224
80% Torsional strength (ft-lbs)	84,391
Burst Pressure capacity (psi)	<u>14,517</u> 10.820
Collapse capacity (psi)	10,020
FOOL JOINT	
Dimensional Data	New
OD (in)	7.000
ID (in)	4.000
Pin tong length (in)	10
Box tong length (in)	12
Connection	DPDS55
Performance Data	New
Torsional Strength (ft-lbs)	74,167
Max Recommended Make-up Torque (ft-lbs)	44,500
Min Recommended Make-up Torque (ft-lbs)	33,375
Tensile strength (lbs)	1,292,500
Tool joint/Drill pipe torsional ratio (New pipe)	0.70
Drill pipe assembly with DPDS55 tool joint	
Drill pipe assembly with DPDS55 tool joint Average length (ft)	31.5
Drift size (in)	3.875
Make & Break: 3 cycles	3.070

Note: Tool Joint and Pipe body values were derived as per API RP 7G and DS1 Latest edition. The above values are for refrence only. DPI LLC is not responsible or liable for any loss or damage or injury resulting from the use of above information.